

MATERIAL SAFETY DATA SHEET

According to 29 CFR 1910.1200(g)



Date Issued: 08/26/2009
 MSDS No: 10015V
 Date-Revised: 08/26/2009
 Revision No: 1

E-Z Wax® Paste-Yellow**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: E-Z Wax® Paste-Yellow
GENERAL USE: Automotive reconditioning product
PRODUCT DESCRIPTION: Automotive Paste Wax
PRODUCT CODE: 15
PRODUCT FORMULATION NAME: E-Z Wax® Paste-Yellow

MANUFACTURER

Auto Wax - An ITW Company
 Auto Magic®
 1275 Round Table Drive
 Dallas TX 75247

Product Stewardship: 1-800-826-0828
Transportation: 1-800-826-0828
Service Number: 1-214-631-4000
 Auto Wax - An ITW Company
 Auto Magic®

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-826-0828

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****IMMEDIATE CONCERNS:** Harmful if swallowed.**POTENTIAL HEALTH EFFECTS****EYES:** Moderately irritating to the eyes.**SKIN:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).**INGESTION:** Harmful if swallowed.**INHALATION:** Prolonged or excessive inhalation may cause respiratory tract irritation.**SIGNS AND SYMPTOMS OF OVEREXPOSURE****ACUTE TOXICITY:** May cause headaches and dizziness.**MEDICAL CONDITIONS AGGRAVATED:** dermatitis may be aggravated by excessive exposure to skin.**ROUTES OF ENTRY:** include skin contact, eye contact and ingestion**TARGET ORGAN STATEMENT:** not established**CANCER STATEMENT:** not established**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt. %	CAS	EINECS	Classification
Odorless Mineral Spirits	40 - 50	64742-48-9	265-150-3	Xn; R10-65-66-67
Kerosine (petroleum) (Kerosene)	5 - 10	8008-20-6	232-366-4	Xn; R65-66
Distillates (petroleum) hydrotreated light	10 - 20	64742-47-8	265-149-8	Xn; R65

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Seek medical attention if irritation persists.

SKIN: Wash with soap and water.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

INHALATION: Move to fresh air

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: ~ 43°C (109°F) TCC

FLAMMABLE LIMITS: not available

AUTOIGNITION TEMPERATURE: not established

GENERAL HAZARD: Combustible liquid. Keep away from heat and open flame.

EXTINGUISHING MEDIA: use foam, dry chemical or carbon dioxide extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: not established

FIRE FIGHTING PROCEDURES: not established

SENSITIVE TO STATIC DISCHARGE: not established

SENSITIVITY TO IMPACT: not established

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and collect with absorbent

LARGE SPILL: LARGE SPILLS: Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent. Proper disposal of absorbent is required after use.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

STORAGE TEMPERATURE: 4°C (40°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: one year

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)			
		EXPOSURE LIMITS	
		Supplier OEL	
Chemical Name		ppm	mg/m ³
Odorless Mineral Spirits	TWA	300 ppm	1900 mg/m ³
Kerosine (petroleum) (Kerosene)	TWA	400 ppm	
Distillates (petroleum) hydrotreated light	TWA	300 ppm	2300 mg/m ³

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles.

SKIN: Use Nitrile/ Vinyl gloves

RESPIRATORY: NIOSH respirator -(organic vapor) in absence of proper environmental control.

PROTECTIVE CLOTHING: Clean, body-covering clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Specific Gravity
Odorless Mineral Spirits	49	178	0.76
Distillates (petroleum) hydrotreated light	81		0.79

PHYSICAL STATE: Solid

ODOR: hydrocarbon odor

APPEARANCE: Yellow Paste

PERCENT VOLATILE: 75-85

MELTING POINT: > 80°C (180°F)

FLASHPOINT AND METHOD: ~ 43°C (109°F) TCC

SPECIFIC GRAVITY: ~ 0.800 to 0.9 gm/ml

(VOC): < 45.000 % by weight

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
Distillates (petroleum) hydrotreated light	> 5 g/Kg-rat	> 3.16 g/kg - rabbit

CARCINOGENICITY

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

SENSITIZATION: not available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: not available

ECOTOXICOLOGICAL INFORMATION: not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

OTHER SHIPPING INFORMATION: Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. REGULATORY INFORMATION**UNITED STATES****TSCA (TOXIC SUBSTANCE CONTROL ACT)**

TSCA REGULATORY: All Ingredients are on the TSCA Inventory or are not required to be listed on the TSCA Inventory

CANADA**WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Toxic



Combustible Liquid


16. OTHER INFORMATION

PREPARED BY: Tony Casmus

REVISION SUMMARY: Revision #: 1. This MSDS replaces the August 26, 2009 MSDS.

HMIS RATING

HEALTH:	-	1
FLAMMABILITY:		2
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA CODES

MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.