

**Auto Magic**<sup>®</sup>

**TORNADO  
MAGIC**<sup>™</sup> **CLEANING TOOL**

**Kit # TM-300**


**Replacement Instructions for Gun Cap**

Tools Needed:

24 mm open end wrench

24 mm socket

Reversible Ratchet



Step #1: With one hand grasp the cap and air reverse assembly firmly. With the opposite hand grasp the pickup tube where it is attached to the metal inlet and pull firmly. The pickup tube should slip off the metal inlet with a medium amount of force.

Step #2: Place the 24 mm open end wrench on the nut at the top of the cap. This will keep air reverse assembly from moving.

Step #3: Attach the 24 mm socket to the ratchet and place on the nut inside the cap. With one hand use the one end wrench to hold the air reverse assembly in place and with the opposite hand use the ratchet to loosen the nut inside the cap.

Step #4: Remove the cap from the gun. The gasket inside the cap is re-usable so it can be removed and placed inside the new cap. Place the new cap on the gun and by hand, start the nut that was removed.

Step #5: As in Step #3, with one hand use the open end wrench to hold the air reverse assembly in place. Change the ratchet to tighten. Use the opposite hand to hold the ratchet and tighten the nut until snug. **(Do not over tighten nut. Torque should not exceed 45 lbs.)**

Step #6: Re-attach the pickup tube to the gun by sliding it over the metal inlet